

Lithofin TC Classic Wax

Description

A special product from the LITHOFIN-Range for terracotta (TC). This ready-to-use, colourless paste contains high quality natural and synthetic waxes.

Properties

Lithofin TC Classic Wax is easy to apply and distribute. The product forms a wax layer that can be polished to produce the typical (traditional) terracotta look.

Technical Data:

Density: approx. 0.8 g/cm³

pH-Value: n.a.

Flash Point: > 23°C

Appearance: yellowish white, pasty

Odour: aromatic

Solubility in Water: not soluble

Field of Use

For final treatment of terracotta floors that have been pre-treated with Lithofin TC Classic Primer (please refer to Technical Information 141- / 143- for further information).

Waxing the surface is the second step of the so called "classical" method of treating terracotta. The treatment strengthens the colours and leaves an elegant sheen. Lithofin TC Classic Wax is also suitable for touching up waxed surfaces.

The product is not suitable for glazed tiles, highly absorbent surfaces and outdoor use.

Directions for Use

Stir before use if warmed in water bath. Approx. 60 minutes after applying Lithofin TC Classic Primer, apply Lithofin TC Classic Wax to the surface with a sponge, cloth or a nylon pad and work into the surface. Pre-polish after approx. 10 minutes, preferably using a polishing machine.

After approx. 60 minutes, the surface has dried enough for the final polish with a pad or felt or preferably with a polishing machine. Do not walk on the surface for 12 hours.

When touching up a used surface, apply thinly and polish after approx. 10 minutes.

Please Note: on very lightly absorbent surfaces, a pre-treatment may not be necessary.

Try in an inconspicuous area.

Drying Time: approx. 60 minutes until polishing, fully cured after 12 hours.

Coverage: approx. 10m² per litre depending on absorbency, up to 50m² when touching up old surfaces.

Storage

Closed, cool and dry. Shelf life of approx. 3 years.

Environmental Protection

Contains solvents, free of chlorinated hydrocarbons. Disposal: liquid product is classified as special waste. Containers are made of environmentally friendly tin plate. Clean containers can be recycled through collection systems.

Safety

Ingredients: natural and synthetic wax, hydrocarbons, and additives.

Labelling according to EU-Directive 1272/2008(CLP):
GHS Symbol 02, 07, 09, Attention
Flammable liquid and vapour. May cause drowsiness or dizziness. Toxic to aquatic life with long lasting effects. Repeated exposure may cause skin dryness or cracking. Keep out of reach of children. Keep away from heat/sparks/open flames/hot surfaces. – No smoking. Use only outdoors or in a well-ventilated area. Immediately call a POISON CENTER or doctor/physician. Store locked up.

ADR 2015: labelling for transport		
Unit	Label	Notes on freight papers
a) b)	LQ	none, due to limited quantities

Packaging

- a) 1 litre bottle with child-proof cap (10 per box)
- b) 5 litre canister (2 per box)

Please Note: statements concerning environmental and safety issues refer to the product as delivered (concentrated). This information should be considered to be informal and non-binding. The products must be used according to local conditions and materials. Always test the product in an inconspicuous area. (GB8.15gps/6.15)

Distribution in UK and Ireland:

CASDRON Enterprises Ltd. • Alresford, Hampshire SO24 9QF • Phone: +44 (0)1962 732 126 • sales@lithofin.co.uk

Manufactured in Germany by: LITHOFIN AG • 73240 Wendlingen • e-mail: info@lithofin.de

www.lithofin.co.uk